

- √ Support two-way video call
- √ Support video from dual monitoring device
- √ AI voice activation
- √ One-click video call on device
- √ Support Bluetooth connection



Specification

Model No.:	ICS-PT17	
APP	ICSee	
System	Main control chip processor	Dual-core 32-bit DSP (XM650V200)
	Image Sensor	1/3-inch low-light CMOS sensor
	operating system	Embedded LINUX operating system
	Image encoding format	Smart H.265X
Video	Effective video pixels	3MP
	Resolution	Main Stream: 2304*1296@12fps; Sub Stream: 800*448@12fps
	Minimum illumination	Color: 0.01Lux@(F1.2,AGC ON);0 Lux with IR;
		Black and White: 0.001Lux@(F1.2,AGC ON);0 Lux with IR;
	lens	3.6mm
	perspective	92°
video flip	Flip up and down / Flip left and right	
Screen	Size	2.4" IPS HD Screen
	Resolution	320*240
Night Vision	Light control mode	IR
	Number of fill lights	6pcs
PTZ	PTZ control	horizontal: 350°; vertical: 90°
	PTZ flip	Flip up and down / Flip left and right
Audio	Coding standards	G.711
	Pickup	Support
	Trumpet	Support
Video management	Video file size	≈6G/天
	Video recording method	Manual recording, dynamic detection recording, scheduled recording, alarm recording
	Video save	TF card/Cloud
	Storage	Cloud storage + TF local recording (up to 128GB)
	Remote playback	Support
	Capture function	Support
Alarm	Humanoid detection	Support
	Regional alert	Support
	Alarm message push	Support

Internet function	Wireless network	2.4G WIFI 802.11b/g/n
	Distribution network	Bluetooth fast distribution network
Others	Reset button	Support
	Business functions	Support two-way video intercom, mobile remote monitoring, and alarm message push
	Humanoid tracking	Support
	360 degree positioning	Support
Supply	Power supply	DC 5V 1A
	Power interface	Type-C
Environment	Applicable places	Homes, shops, supermarkets, factories and other places;
	Installation method	Wall-mounted and desktop-mounted
	Operating temperature	-20°C - +55°C
	Working humidity	10% - 90%
www.innotronik.com		