



Product feature	• HD double shot double frame		
	• Video intelligent linkage account the overall situation and details		
	• Ultra-low power standby 0.2 seconds quick wake up video capture		
	• PIR human body sensing +Ai humanoid detection alarm		
	• High performance ISP+1/2.7" black light image sensor		
	• Support Two-ways Audio		
	• Supports cloud storage and local storage.		
	• The APP supports Android/ Apple IOS		
	• 6W solar panel can be universal adjustment, integrated/separate installation		
Model	UB-PT30-4G(2MP)		
	Resolution	4MP=2Mp+2Mp	
General	Pixel	1920*1080P+1920*1080P	
	Main processor	Ingenic-T40N	
	Image sensor	GC2063	
	APP operate system	Android, Apple IOS	
	Compressed format	H.265	
Lens	Focal length	Wide Angle lens 2.8mm ball machine lens 6mm	
	Angle	Wide Angle lens 110° ball machine lens 48°	
Internet connection	4G	TD-LTE,TD-LTE / LTE FDD TD-LTE / LTE-FDD	
	4G mode version	China	LTE-FDD B1/B3/B5/B8 LTE-TDD B34/B38/B39/B40/B41
		Southeast Asia	LTE-FDD B1/B3/B5/B8 LTE-TDD B34/B38/B39/B40/B41
		European	LTE-FDD: B1/B3/B5/B7/B8/B20/B28
		GSM Version	LTE FDD:B1/B2/B3/B4/B5/B7/B8/B12/B13/18/B19/20/B25/B26/B28/B66 LTE-TDD:B38/B39/B40/B41
		America	LTE-FDD: B2/B4/B5/B12/B13/B25/B26
		Japan	LTE-FDD:B1/B3/B8/B18/B19/B26
Alarm mode	Detection mode	PIR Human sensing +AI human detection	
	Detection range	0-12M	
	Detection angle	110°+ 110°	
	Alarm mode	Real time mobile phone calling or push message	
PTZ	PTZ angle	355 ° Horizontal and 100° vertical	
	Rotational speed	Horizontal 55°/ s Vertical 40°/ s	
Night vision mode	night vision	Illuminance is 0.00LUX	
	infrared light	Infrared LED distance 30M	
	White light	White LED distance 30M	

Voice	Built-in speaker	3W
	Built-in microphone	Monitor range 20M
Storage	Video mode	Alarm video/timing video/all-day video
	Cloud storage	Cloud storage (alarm event video)
	Local storage	TF card (Max 128G)
Power	Power supply mode	Solar panel + battery
	Solar battery sheet material	Monocrystalline silicon
	Solar battery power	6W
	Battery	3pcs 21700 battery
	Max working power	4.5W
	Standby power	0.003W
Other	Working area	Indoor/outdoor
	working temperature	-30°~+60°
	Working humidity	0%~90%RH
Package	Net weight	1.35KG
	Box size	195*190*165mm
	Packing quantity	9PCS
	Gross weight	12.95KG
	Carton size	570*195*495mm
www.innotronik.com		